

Office Fax TF4020

Thermal transfer fax & copier

Small and reliable

The thermal transfer fax machine convinces through its small size. It can be easily put anywhere in your home or your small office.



Solid communication functions

- Each fax transfer finishes with a sending report with reduced first page
- Predefined fax forms and the timer function ease the workflow
- Send a fax to multiple receivers via the group-broadcasting feature
- Store up to 50 name dial entries and dedicate distinctive ring tones to special fax senders
- The automatic document feeder has a capacity of up to 10 pages for larger documents

Convenience and safety

- More security through a 15 page memory
- The space saving design makes it easy to find room for the device
- The timer function allows you to postpone the dispatch of your faxes up to 24 hours
- 10 short dial keys, which can be set up for your most frequent fax receivers, help you save time

Office Fax TF4020

Thermal transfer fax & copier

Small, multifunctional and reliable



Office Fax TF4020	
Fax	
Speed	9.6 Kbps
Resolution	up to 200 x 200 dpi
Memory	up to 50 pages
Copy	
Multicopy	up to 15 pages
Paper handling	
Paper input	50 sheets paper tray
Document feeder	up to 10 sheets
Duty cycle	
	up to 100 pages/month

Fax

ITU Group 3 compatible (T.30 standard/T.30 new)
 9.6 Kbps modem speed, auto fall back
 Horizontal resolution: 8 pixels/mm
 vertical resolution standard: 3.85 lines/mm
 vertical resolution fine: 7.7 lines/mm
 Page header, automatic redial
 Sending report with reduced copy of the first page
 Printing method: thermal transfer
 10 page automatic document feeder (ADF)
 5 Predefined fax forms
 Timer function (send later)
 Up to 15 page memory
 Group broadcasting
 Easy polling (receive and send)
 Paper tray up to 50 sheets
 Cordless phone management
 Up to 50 name dial entries
 10 ringer melodies
 10 short dial keys
 6 speed dial keys
 Chain dialling
 Redial of the last 10 numbers
 Caller identification (CLIP)*

Copier

Multicopy up to 15 pages
 Fine-/photo-resolution
 Zoom-function (enlarge/reduce)
 16 grey scales

Operating Environment

Operating Temperature: 5° - 40° C
 Humidity: 15 – 85 %

Electrical

Power: 195 – 264V, 47 – 63 Hz
 Stand by: <1,5 W
 Transmission: typ. 15 W
 Reception: typ. 15 W
 Copy: typ. 15 W

Dimensions (WxDxH)

Unpacked: 313x195x126 mm
 Packed: 380x250x200 mm
 Weight unpacked: 2.2 kg
 Weight packed: 2.9 kg

What comes in the box:

Fax machine incl. cables (mains and telephone network)
 Starter Inkfilm
 User manual including installation guide

Supplies

Inkfilm Xerox TC401
 Inkfilm Xerox TC402

General Information

9 NC: 28814XXXX
 Type number: TF4020/XX
 EAN-Code: 342516027XXXX

* Depends on the availability of the service on the local operators network

www.xeroxfax.com

Xerox® and the sphere of connectivity are trademarks of Xerox Corporation in the US and/or other countries and used under license.

Design © 2009 Xerox Corporation. Contents © 2009 SAGEM Communications Austria GmbH. All rights reserved. The information and specifications included are subject to change without prior notice. SAGEM Communications tries to ensure that all information in this document is correct, but does not accept liability for error or omission.

